

imageRUNNER ADVANCE DX C5800 Series

POWERFUL PRODUCTIVITY FROM SECURE COLOUR A3 MULTIFUNCTION DEVICES



Canon uniFLOW Online
Outstanding Cloud Output Management Solution




Canon uniFLOW Online
Outstanding Cloud Output Management Solution



New to the Line

MAIN CONFIGURATION OPTIONS



This flat configuration is for illustration purpose only. For a complete list of options and the exact compatibility relationships, please refer to the [online product configurator](#).

The Unified Firmware Platform (UFP) ensures that the latest feature upgrades and protection are available, for an enhanced user experience across the entire IR ADVANCE DX portfolio.

*To support Sustainability and save on raw materials required for plastics, 1st Copy Tray Kit-A1 is optional.

Canon

TECHNICAL SPECIFICATIONS

imageRUNNER ADVANCE DX C5800 Series

MAIN UNIT	A3 Color Laser Multifunctional	Fonts	PS fonts: 136 Roman PCL fonts: 93 Roman, 10 Bitmap fonts, 2 OCR fonts, Andale Mono WT J/K/S/T* (Japanese, Korean, Simplified and Traditional Chinese), Barcode fonts**
Machine type	Print, Copy, Scan, Send, Store and Optional Fax		
Core functions	1.8GHz Dual Core Processor		
Processor	10.1" TFT LCD WSVGA Color Touch panel (up to 90° tiltable)		
Control Panel	Standard: 5,0GB RAM		
Memory	Standard: (SSD) 256GB, Optional: (SSD) 256GB, 1TB	Print Features	Secured Print, Secure Watermark, Header/Footer, Page Layout, Two-sided Printing, Mixed Paper Sizes/Orientations, Front/Back Covers, Toner Reduction, Poster Printing, Forced Hold printing, Print Date, Scheduled Printing, Printing Using a Virtual Printer
Storage	NETWORK Standard: 1000Base-T/100Base-TX/10Base-T, Wireless LAN (IEEE 802.11 b/g/n), Optional: NFC, Bluetooth Low Energy	Operating System	UFR II: Windows* 8.1/10/Server2012/Server2012 R2/Server2016/Server2019, Mac OS X(10.11 or later) PCL: Windows* 8.1/10/Server2012/Server2012 R2/Server2016/Server2019 PS: 8.1/10/Server2012/Server2012 R2/Server2016/Server2019, Mac OS X(10.11 or later) PPD: Windows* 8.1/10, Mac OS X(10.10 or later) McAfee Embedded Control Software As of Oct. 2020
Interface Connection	OTHERS Standard: USB 2.0 (Host) x1, USB 3.0 (Host) x1, USB 2.0 (Device) x1, Optional: Serial Interface, Copy Control Interface		
Paper Supply Capacity (A4, 80gsm)	Standard: 1,200 sheets 100-sheet Multi-purpose tray x 1 550-sheet Paper cassette x 2, Maximum: 6,350 sheets (with High Capacity Cassette Feeding Unit-C1 + Paper Deck Unit-F1)	COPY SPECIFICATIONS	
Paper output capacity (A4, 80gsm)	Maximum: 3,450 Sheets (with Staple Finisher-AB1 or Booklet Finisher-AB1 and 3rd Copy Tray Kit-A1)	Copy Speed (BW & CL)	iR-ADV DX C5870i up to 70 ppm (A4, A5*, A5R, A6R), up to 36 ppm (A3), up to 42 ppm (A4R)
Finishing capabilities	Collate, Group, Offset, Staple, Saddle Stitch, Hole Punch, Eco Staple, Staple On Demand * Finishing capabilities will vary depending on the options connected.	* 1-sided only	iR-ADV DX C5860i up to 60 ppm (A4, A5*, A5R, A6R), up to 32 ppm (A3), up to 36 ppm (A4R)
Supported Media Types	Multi-purpose tray: Thin, Plain, Recycled, Color, Heavy, Coated, Tracing, Bond, Transparency, Label, Pre-punched, Letterhead, Tab, Envelope Paper Cassette (Upper/Lower): Thin, Plain, Recycled, Color, Heavy, Bond, Transparency, Pre-punched, Letterhead, Envelope* * Envelope Feeder Attachment (standard) is required.		iR-ADV DX C5850i up to 50 ppm (A4, A5*, A5R, A6R), up to 27 ppm (A3), up to 30 ppm (A4R)
Supported Media Sizes	Multi-purpose tray: Standard size: SR-A3, A3, A4, A4R, A5, A5R, A6R, B4, B5, B5R Custom size: 98.0 x 139.7 mm to 320.0 x 457.2 mm Free Size: 98.0 x 139.7 mm to 320.0 x 457.2 mm Envelopes: COM 10 No.10, Monarch, DL, ISO-C5 Envelope custom size: 98.0 x 90.0 mm to 320.0 x 457.2 mm Upper Cassette: Standard size: A4, A5, A5R, A6R, B5 Custom Size: 98.0 x 148.0 mm to 297.0 x 215.9 mm Envelopes: COM10 No.10, Monarch, DL, ISO-C5 Lower Cassette: Standard size: A3, A4, A4R, A5, A5R, A6R, B4, B5, B5R Custom size: 98.0 x 148.0 mm to 304.8 x 457.2 mm Envelopes: COM10 No.10, Monarch, DL, ISO-C5		iR-ADV DX C5840i up to 40 ppm (A4, A5*, A5R, A6R), up to 21 ppm (A3), up to 24 ppm (A4R)
Supported media weights	Multi-purpose tray: 52 to 300 gsm Paper Cassette (Upper/Lower): 52 to 256 gsm Duplex: 52 to 256 gsm	First-Copy-Out Time (A4, BW/CL)	iR-ADV DX C5870i: Approx. 2.7 / 3.7 seconds or less iR-ADV DX C5860i: Approx. 2.9 / 4.2 seconds or less iR-ADV DX C5850i: Approx. 3.4 / 4.9 seconds or less iR-ADV DX C5840i: Approx. 4.1 / 6.1 seconds or less 600 x 600 Up to 999 copies Automatic or Manual (9 Levels) Copy Density Magnification Variable zoom: 25% to 400% (1% Increments) Preset reduction/enlargement: 25%, 50%, 70%, 100%(1:1), 141%, 200%, 400%
Warm-up Time	Quick Startup Mode: 4 Seconds or less* * Time from device power-on to when the copy icon appears and is enabled to operate on the touch panel display. From Sleep Mode: 7 Seconds or Less (iR-ADV DX C5870i) 6 Seconds or Less (iR-ADV DX C5860i/C5850i/C5840i) From Power On: 6 Seconds or less (with Quick Start Mode)* * Time from device power-on, until copy ready (not print reservation).		iR-ADV DX C5870i: Approx. 4.1 / 6.1 seconds or less 600 x 600 Up to 999 copies Automatic or Manual (9 Levels) Copy Density Magnification Variable zoom: 25% to 400% (1% Increments) Preset reduction/enlargement: 25%, 50%, 70%, 100%(1:1), 141%, 200%, 400%
Dimensions (W x D x H)	iR-ADV DX C5870i/C5860i/C5850i/C5840i: 620 x 722 x 937 mm	Copy resolution (dpi)	600 x 600
Installation Space (W x D)	iR-ADV DX C5870i/C5860i/C5850i/C5840i: Basic: 1,138 x 1,162 mm (Right Cover Open with Multi-purpose tray extended + Cassette Drawers Open) Fully Configured: 1,866 x 1,162 mm (Staple Finisher-AB1/Booklet Finisher-AB1 with the extension tray extended + Paper Deck Unit-F1 + Cassette Drawers open)	Multiple Copies	Up to 999 copies
Weight	iR-ADV DX C5870i: Approx. 108 kg including regular toner iR-ADV DX C5860i/C5850i: Approx. 105 kg including regular toner iR-ADV DX C5840i: Approx. 104 kg including regular toner	Copy Density	Automatic or Manual (9 Levels)
PRINT SPECIFICATIONS		Magnification	Variable zoom: 25% to 400% (1% Increments) Preset reduction/enlargement: 25%, 50%, 70%, 100%(1:1), 141%, 200%, 400%
Print Speed (BW/CL)	iR-ADV DX C5870i up to 70 ppm (A4, A5*, A5R, A6R), up to 36 ppm (A3), up to 42 ppm (A4R)	Copy Features	Preset R/E Ratios by Area, Two-Sided, Density Adjustment, Original Type Selection, Interrupt Mode, Book to Two Pages, Two-sided Original, Job Build, N on 1, Add Cover, Insert Sheets, Different Size Originals, Page Numbering, Copy Set Numbering, Sharpness, Erase Frame, Secure Watermark, Print Date, Gutter, Print & Check, Negative/Positive, Repeat Images, Merge Job Blocks, Mirror Image, Store in Mail Box, Superimpose Image, Copy ID Card, Skip Blank Pages, Free Size Original, Color Mode, Reserved Copy, Copy Sample
* 1-sided only	iR-ADV DX C5860i up to 60 ppm (A4, A5*, A5R, A6R), up to 32 ppm (A3), up to 36 ppm (A4R)	SCAN SPECIFICATION Type	Single-pass Duplexing Automatic Document Feeder* [2-sided to 2-sided (Automatic)] * Detect Feeder Multi Sheet Feed is supported, up to 200 Sheets
	iR-ADV DX C5850i up to 50 ppm (A4, A5*, A5R, A6R), up to 27 ppm (A3), up to 30 ppm (A4R)	Document Feeder Paper Capacity (80 gsm)	Platen: Sheet, Book, and 3-Dimensional Objects Document Feeder media weight: 1-sided scanning: 38 to 220 gsm (BW, CL) 2-sided scanning: 38 to 220 gsm (BW, CL) * An acceptable weights of A6R or smaller is 50 to 220gsm.
	iR-ADV DX C5840i up to 40 ppm (A4, A5*, A5R, A6R), up to 21 ppm (A3), up to 24 ppm (A4R)	Acceptable Originals and weights	Platen scanning size: up to 297.0 x 431.8 mm Document Feeder media size: A3, A4, A4R, A5, A5R, A6R, B4, B5, B5R, B6R Custom size: 70.0 x 139.7 mm to 304.8 x 431.8 mm
Print Resolution (dpi)	1,200 x 1,200	Supported media sizes	1-sided Scanning: 135/135 (300 x 300 dpi, send), 80/80 (600 x 600 dpi, copy), 2-sided Scanning: 270/270 (300 x 300 dpi, send), 160/90 (600 x 600 dpi, copy)
Page description languages	Standard: UFR II, PCL6, Adobe® PostScript®3™	Scan Speed (ipm: BW/CL; A4)	1-sided Scanning: 135/135 (300 x 300 dpi, send), 80/80 (600 x 600 dpi, copy), 2-sided Scanning: 270/270 (300 x 300 dpi, send), 160/90 (600 x 600 dpi, copy)
Direct Print	Supported file types: PDF, EPS, TIFF/JPEG, and XPS AirPrint, Mopria, Universal Print by Microsoft	Scan Resolution (dpi)	Scan for Copy: 600 x 600 Scan for Send: (Push) 600 x 600 (SMB/FTP/WebDAV/IFAX), (Pull) 600 x 600 Scan for Fax: 600 x 600
Printing from mobile and cloud	Canon PRINT Business and uniFLOW Online (optional) A range of software and MEAP-based solutions are available to provide printing from mobile devices or internet-connected devices and cloud-based services depending on your requirements. Please contact your sales representative for further information.	Pull Scan Specifications	Color Network ScanGear2, For both TWAIN and WIA Supported OS: Windows* 8.1/10/Server2012/Server2012 R2/Server 2016 As of Mar. 2020
		Scan Method	Push Scan, Pull Scan, Scan to Box, Scan to Advanced Space, Scan to Network, Scan to USB Memory Key, Scan to Mobile devices, Scan to cloud (uniFLOW Online - Optional)
		SEND SPECIFICATIONS	
		Destination	Standard: E-mail/Internet FAX (SMTP), SMB3.0, FTP, WebDAV, Mail Box Optional: Super G3 FAX, IP Fax LDAP (2,000)/Local (1,600)/Speed dial (200)
		Address Book	Push: up to 600 x 600 Pull: up to 600 x 600
		Send resolution (dpi)	File: FTP(TCP/IP), FTPS (encrypted FTP), SMB3.0 (TCP/IP), WebDAV E-mail, I-Fax: SMTP, POP3
		Communication protocol	

TECHNICAL SPECIFICATIONS

imageRUNNER ADVANCE DX C5800 Series

File Format	TIFF, JPEG, PDF (Limited Color, Compact, Searchable, Apply policy, Optimize for Web, PDF/A-1b, Trace & Smooth, Encrypted, Device Signature, User Signature), XPS (Compact, Searchable, Device Signature, User Signature), Office Open XML (PowerPoint, Word)	Power consumption	Maximum: Approx. 2,000 W (iR-ADV DX C5870i) Approx. 1,800 W (iR-ADV DX C5860i/C5850i/C5840i) Copying (with DADF continuous scan): Approx. 943 W** Standby: Approx. 53.4 W* Sleep mode: Approx. 0.8 W** * Reference value: measured one unit ** 0.8 W is not available in all circumstances due to certain settings.
Universal Send Features	Original Type Selection, Two-sided Original, Book to Two Pages, Different-size Originals, Density Adjustment, Sharpness, Copy Ratio, Erase Frame, Job Build, Delayed Send, Preview, Job Done Notice, File Name, Subject/Message, Reply-to, E-mail Priority, TX Report, Original Content Orientation, Skip Blank Pages	Noise levels (BW/CL)	Typical Electricity Consumption (TEC)* : iR-ADV DX C5870i: 0.86 kWh iR-ADV DX C5860i: 0.71 kWh iR-ADV DX C5850i: 0.58 kWh iR-ADV DX C5840i: 0.46 kWh * As per USA Energy Star 3.0
FAX SPECIFICATIONS	(Optional)		Sound Power Level (LWA,m) Active (BW) (1-sided) iR-ADV DX C5870i: 66 dB*, Kv 3 dB* iR-ADV DX C5860i: 64 dB*, Kv 3 dB* iR-ADV DX C5850i: 62 dB*, Kv 3 dB* iR-ADV DX C5840i: 61 dB*, Kv 3 dB* * Reference value: measured only one unit with ISO7779, described with ISO9296 (2017)
Maximum Number of Connection Lines	2 (2nd line optional)		Sound Pressure (LpAm) Bystander's position: Active (BW/CL) (1-sided) iR-ADV DX C5870i: 52 dB*/52 dB* iR-ADV DX C5860i: 50 dB*/51 dB* iR-ADV DX C5850i: 48 dB*/49 dB* iR-ADV DX C5840i: 47 dB*/47 dB*
Modem Speed	Super G3: 33.6 kbps G3: 14.4 kbps		Stand-by iR-ADV DX C5870i/C5860i/C5850i: 23 dB* * Reference value: measured only one unit with ISO7779, described with ISO9296 (2017)
Compression Method	MH, MR, MMR, JBIG	Standards	Blue Angel
Resolution (dpi)	400 x 400 (Ultra Fine), 200 x 400 (Super Fine), 200 x 200 (Fine), 200 x 100 (Normal)	CONSUMABLES	
Sending/Receiving Size	Sending: A3, A4, A4R, A5*, A5R*, B4, B5*, B5R** Receiving: A3, B4, A4, A4R, A5R, B5, B5R * Sent as A4 ** Sent as B4 short	Toner Cartridges	C-EXV 58 Toner BK/C/M/Y C-EXV 58L Toner C/M/Y
FAX memory	Up to 30,000 pages (2,000 jobs)	Toner Yield (Estimated Yield @5% coverage)	C-EXV 58 Toner BK: 71,000 pages C-EXV 58 Toner C/M/Y: 60,000 pages C-EXV 58L Toner C/M/Y: 26,000 pages
Speed dials	Max. 200	SOFTWARE AND PRINTER MANAGEMENT	For detailed information please visit our website https://www.canon-europe.com/business/universal_login_manager/ulm/
Group dials/destinations	Max. 199 dials	Tracking and reporting	uniFLOW Online Express*
Sequential broadcast	Max. 256 addresses	Remote management tools	* For more information, please refer to uniFLOW Online Express
Memory backup	Yes	Scanning software	iWEMC
Fax Features	Sender's Name (TTI), Selecting the Telephone Line (when sending fax), Direct Send, Delayed Send, Preview, Job Done Notice, TX Report, Interrupt Transmission, Sequential Broadcasting, Password/Subaddress Sending, Confidential Mailbox, 2 on 1 Log	Optimisation tools	eMaintenance
STORE SPECIFICATIONS		Platform	Content Delivery System
Mail Box (Number supported)	100 User Inboxes, 1 Memory RX Inbox, 50 Confidential Fax Inboxes Maximum 10,000 Pages (2,000 jobs) Stored	Document Publishing	Network ScanGear
Advanced Space	Communication Protocol: SMB or WebDAV Supported Client PC: Windows* 8.1/10 Concurrent Connections (Max.): SMB:64, WebDAV:3	FIERY PRINT CONTROLLER SPECIFICATIONS (EMBEDDED)	Canon Driver Configuration Tool
Advanced Space available disc space	Standard:16 GB (With option: max. 480GB)	Name	MEAP (Multifunctional Embedded Application Platform)
Advanced Space Features:	Authentication for Advanced Space Log-in, Sort Function, Printing a PDF File with a Password, imageWARE/Secure Audit Manager Support, Search, File Preview, Authentication Management, Open to public, URI TX, Backup/Restore	Print Resolution (dpi)	Kofax PowerPDF Advanced (Optional)
SECURITY SPECIFICATIONS		Page Description Language(s)	
Authentication and Access Control (Activation is required)	User Authentication (Picture Login, Picture and PIN Login, Card Login*, Username and Password Login, Function Level Login, Mobile Login), Department ID Authentication (Department ID and PIN Login, Function Level Login), uniFLOW Online Express (PIN Login, Picture Login, Picture and PIN Login, Card Login*, Card and PIN Login, Username and Password Login, Department ID and PIN Login, Function Level Login), Access Management System (Access Control)	Memory	For full specifications & options, please visit the Canon website Optional on all models
Document Security	* Card readers are optional, please refer to Hardware Accessories Print Security (Secure Print, Encrypted Secure Print, Forced Hold Printing, uniFLOW Secure Print**), Receive Data Security (Confidential Fax Inbox Forwarding Received Documents Automatically), Scan Security (Encrypted PDF, Device Signature PDF/XPS, User Signature PDF/XPS, Adobe LiveCycle® Rights Management ES2.5 Integration), BOX Security (Mail Box Password Protected, Advanced Space Access Control), Send Data Security (Setting for requesting password input per transmission, Restricted E-mail/File send functions, Confirming FAX number, Allow/Restrict Fax Driver Transmissions, Allow/Restrict Sending from History, S/MIME Support), Document Tracking (Secure Watermark) ** Requires uniFLOW Online / uniFLOW	Hard Disk Drive	imagePASS-R1 (Embedded)
Network Security	TLS 1.3, IPsec, IEEE802.1X authentication, SNMP V3.0, Firewall Functionality (IP/MAC Address Filtering), Dual Network Support (Wired LAN/Wireless LAN, Wired LAN/Wired LAN), Disabling Unused Functions (Enabling/Disabling Protocols/Applications, Enabling/Disabling Remote UI, Enabling/Disabling USB Interface), G3 FAX separation from LAN, USB Port separation from LAN, Prohibit the execution of files stored in Advanced Box in the MFP, Scan and Send -Virus Concerns for E-mail Reception	Processor Speed	1200 x 1200, 600 x 600
Device Security	Protecting SSD Data (SSD Data Encryption (FIPS140-2 Validated), SSD Lock, Standard SSD Initialize, Trusted Platform Module (TPM 2.0), Job Log Conceal Function, Protecting MFD Software Integrity, Checking MFD Software Integrity (Verify System at Startup, Runtime Intrusion Detection), HCD-PP* * Certification will follow post launch of this Series	System	Adobe PS3, PCL6
Device Management and Auditing	Administrator Password, Digital Certificate And Key Management, Audit Log, Cooperating with External Security Audit System (Security Information and Event Management), Image Data Logging, Security Policy Setting	PAPER SUPPLY OPTIONS	4GB (1x4GB)
ENVIRONMENTAL SPECIFICATIONS		Cassette Feeding Unit-AQ1	500 GB SATA
Operating Environment	Temperature: 10 to 30 °C Humidity: 20 to 80 % RH (Relative Humidity)	High Capacity Cassette Feeding Unit-C1	Intel Pentium G4400 (3.3GHz)
Power source	220-240 V, 50/60 Hz, 6 A	Paper Deck Unit-F1	FS400
		OUTPUT OPTIONS*	
		1st Copy Tray Kit-A1	



TECHNICAL SPECIFICATIONS

imageRUNNER ADVANCE DX C5800 Series

Inner 2way Tray-M1

Tray Capacity (with 80 gsm paper)
Upper tray: A4, A5, A5R, A6R, B5: 100 sheets
SRA3, A3, A4R, B4, B5R: 50 sheets
Lower tray: A4, A5, A5R, A6R, B5: 100 sheets
SRA3, A3, A4R, B4, B5R: 100 sheets

Paper Weight: 52 to 300 gsm
Dimensions (W x D x H): 428 x 405 x 88 mm
Weight: Approx. 0,7 kg

3rd Copy Tray Kit-A1

Capacity (with 80gsm paper):
A4, A5R, B5: 100 sheets
A3, A4R, B4, B5R: 75 sheets
Paper Weight: 52 to 300 gsm
Dimensions (W x D x H): 442 x 373 x 176 mm
(attached to the main unit, when the extension tray is extended)
Weight: 0.5 kg

Inner Finisher-L1 (Not supported for iR-ADV DX C5870)

Tray Capacity (with 80gsm paper):
Upper Tray: SRA3, A3, A4, A4R, A5, A5R, A6R, B4, B5, B5R: approx 45 sheets
Lower Tray: A4, A5, A5R, B5: approx. 500 sheets,
SRA3, A3, A4R, B4, B5R: 250 sheets,
A6R: 30 sheets
Envelope: 10 sheets

Paper Weight: 52 to 300 gsm
Staple Position: Corner, Double
Staple Capacity: (52 to 90 gsm paper)
A4, B5: 50 sheets

A4R: 40 sheets
A3, B4: 30 sheets
Eco Staple*:
A4, B5: 10 sheets (52 to 64 gsm)
8 sheets (65 to 81,4 gsm)
6 sheets (82 to 105 gsm)

A3, B4: 5 sheets (52 to 64 gsm)
4 sheets (65 to 81,4 gsm)
3 sheets (82 to 105 gsm)

Staple On Demand: 40 sheets (80 gsm)
Dimensions (W x D x H): 743 x 525 x 225 mm
(attached to the main unit, when the extension tray is extended)

Weight: Approx. 9,1 kg
* Large size media A3/B4 support will be available from March 2021 when an update to the firmware is applied.

A3*, B4*: 10 sheets (52 to 64 gsm)
8 sheets (65 to 81,4 gsm)
6 sheets (82 to 105 gsm)

Staple Finisher-AB1

(Requires Buffer Pass Unit-P1)
Tray Capacity (with 80gsm paper):
Upper Tray: A4, A5, A5R, A6R, B5: approx. 250 sheets,
SRA3, A3, A4R, B4, B5R: approx. 125 sheets
Lower Tray: A4, A5, A5R, B5: 3,000 sheets,
SRA3, A3, A4R, B4, B5R: 1,500 sheets,
A6R: 250 sheets
Envelopes: Monarch: 30 sheets, COM10 No.10, DL, ISO-C5: 100 sheets

Paper Weight:
Upper Tray 52 to 256 gsm,
Lower Tray 52 to 300 gsm
Staple Position: Corner, Double
Staple Capacity: (52 to 90 gsm)
A4, B5: 50 sheets
A4R: 40 sheets
A3, B4: 30 sheets
Eco Staple*:
A4: 10 sheets (52 to 64 gsm)
8 sheets (65 to 81,4 gsm)
6 sheets (82 to 105 gsm)

A3: 5 sheets (52 to 64 gsm)
4 sheets (65 to 81,4 gsm)
3 sheets (82 to 105 gsm)

Staple On Demand: 50 sheets (52 to 90 gsm)
Dimensions (W x D x H): 637 x 623 x 1,142 mm
(when the extension tray is extended)
Weight: Approx. 31 kg
* Large size media A3 support will be available from March 2021 when an update to the firmware is applied

A3*: 10 sheets (52 to 64 gsm)
8 sheets (65 to 81,4 gsm)
6 sheets (82 to 105 gsm)

Booklet Finisher-AB1

(Requires Buffer Pass Unit-P1)
(Includes the above Staple Finisher-AB1 basic staple specifications)
Saddle Stitch paper size: A3, A4R, B4
Saddle Stitch Staple Capacity: 20 sheets x 10 sets (52 to 81,4 gsm) (including 1 cover sheet 52 to 256 gsm)
Non Staple Folded Bunch Capacity: up to 3 sheets (52 to 105 gsm)
Dimensions (W x D x H): 637 x 623 x 1,142 mm
(when the extension tray is extended)
Weight: Approx. 57 kg

Inner 2/4 Hole Puncher-D1 (Not supported for iR-ADV DX C5870)

(Requires the Inner Finisher-L1)
Two or Four Holes
Acceptable Punch Paper Weight: 52 to 300 gsm
Acceptable Punch Paper Size:
Two holes: A3, A4, A4R, A5, B4, B5, B5R
Four holes: A3, A4

Inner 4 Hole Puncher-D1 (Not supported for iR-ADV DX C5870)

(Requires the Inner Finisher-L1)
Four Holes
Acceptable Punch Paper Weight: 52 to 300 gsm
Acceptable Punch Paper Size:
Four holes: A3, A4, A4R, A5, B4, B5, B5R

2/4 Hole Puncher Unit-A1

(Requires either the Staple Finisher-AB1 or Booklet Finisher-AB1)
Two or Four Holes
Acceptable Punch Paper Weight: 52 to 300 gsm
Acceptable Punch Paper Size:
Two holes: A3, A4, A4R, A5, B4, B5, B5R
Four holes: A3, A4

4 Hole Puncher Unit-A1

(Requires either the Staple Finisher-AB1 or Booklet Finisher-AB1)
Four Holes
Acceptable Punch Paper Weight: 52 to 300 gsm
Acceptable Punch Paper Size:
Four holes: A3, A4, A4R, A5, B4, B5, B5R

HARDWARE ACCESSORIES

Card Readers

Various card readers available e.g. MiCard Plus. Please contact local Canon Office for more details.

Copy Card Reader Attachment-B7
IC Card Reader Box for Numeric Keypad-A1
Copy Card Reader-F1
Printer Cover-M2
Tab Feeding Attachment-F1
Buffer Pass Unit-P1
Utility Tray-B1
Numeric Keypad-A2

Others

SECURITY OPTIONS

Data Security

256GB SSD-A1
1TB SSD-A1
Memory Mirroring Kit-A1

SYSTEM AND CONTROLLER OPTIONS

Print Accessories
Barcode Printing
EFI-Fiery Based Controller
EFI-Fiery Based Controller Options

PCL International Font Set-A1
Barcode Printing Kit-D1
imagePASS-R1
Hot Folders License
Fiery Compose
Fiery Impose
Fiery Impose and Compose
NFC Kit-E2
Serial Interface Kit-K3
Copy Control Interface Kit-A1
Connection Kit-A3 for Bluetooth LE
Super G3 FAX Board-AX1
Super G3 2nd Line Fax Board-AX1
Remote Fax Kit-A1
IP FAX Expansion Kit-B1

System Accessories

Fax Accessories

OTHER OPTIONS

Accessibility Accessories

ADF Access Handle-A1
Voice Guidance Kit-G1
Voice Operation Kit-D1
Staple Cartridge-Y1 (2 x 2,000pcs)*
Staple-P1 (2 x 5,000pcs)
*For Booklet Finisher only

Consumables

Software & Solutions



Certifications and compatibility



Canon Inc.
canon.com
Canon Europe
canon-europe.com
English edition
© Canon Europa N.V., 2020